

Signal Hound®

SM435C Real-Time Spectrum Analyzer



Signal Hound designs and builds powerful, affordable spectrum analyzers and signal generators for engineers, operators and RF professionals around the globe.

REAL-TIME SPECTRUM ANALYSIS UTILIZING A 10 GIGABIT SFP+ PORT - UNPARALLELED SPEED AND PERFORMANCE.

The SM435C is a high-performance spectrum analyzer and monitoring receiver with a 10 Gigabit Ethernet SFP+ port, which enables the SM435C to communicate with a PC over long distances using fiber optic cable. Tuning from 100 kHz to 43.5 GHz, the analyzer has 160 MHz of instantaneous bandwidth (IBW), 110 dB of dynamic range, 1 THz/sec sweep speed at 30 kHz RBW, and ultra-low phase noise to rival even the most expensive spectrum analyzers on the market. As a front-end spectrum analyzer and monitoring receiver, the SM435C provides accurate RF data when it's needed most.

APPLICATIONS

- General Purpose RF Test & Measurement
- EMC pre-compliance
- Phase Noise Characterization
- EVM
- Channel Characterization
- CCDF
- WiFi Characterization
- BlueTooth Characterization
- Calibration
- Manufacturing Test
- RF Power Measurement
- Demodulation
- Antenna Pattern Measurement

FEATURES

- 1 THz/sec Sustained Sweep Speed
- 110 dB of Dynamic Range
- 20 MHz to 43.5 GHz Sub-Octave Preselector
- Spectrum Monitoring
- Ultra-low Phase Noise
- Real-time Analysis Features



Battle Ground, WA 98604 • USA • (360) 313-7997
SignalHound.com • © 2023



SM435C Real-Time Spectrum Analyzer & Monitoring Receiver

May 2023

Preliminary Specifications

Frequency Range	100 kHz to 43.5 GHz		
Sweep Speed	Speed • 1 THz/sec • 160 GHz/sec • 18 GHz/sec	RBW ≥30 kHz 10 kHz 1 kHz	
Displayed Average Noise Level (DANL) REF LEVEL ≤ -20 dBm	Input Frequency Range • 100 kHz to 160 MHz • 160 MHz to 2.2 GHz • 2.2 GHz to 24 GHz • 24 GHz to 36 GHz • 36 GHz to 43.5 GHz	dBm/Hz -156 dBm -159 dBm -155 dBm -153 dBm + 0.5 dB/GHz -147 dBm + 1.1 dB/GHz	
I/Q Acquisition Modes	Calibrated Streaming I/Q: up to 160MHz of selectable I/Q streaming bandwidth		
Timebase Accuracy	• ±5 x 10⁻¹⁰ when locked to GPS • Holdover of ±5 x 10⁻⁹ /day for aging (±2 x 10⁻⁸ first day typ) • Holdover of ±1 x 10⁻⁸ for temperature over -40°C to 65°C (typ)		
System Noise Figure (typ)	• 12 dB over 700 MHz to 2.5 GHz • 15 dB from 2.5 GHz to 24 GHz • 18 dB + 0.5 dB/GHz from 24 GHz to 40 GHz • 26dB + 2.0 dB/GHz from 40 GHz to 43.5 GHz		
Linearity	IP ₂ • 100 kHz to 20 GHz • 20 GHz to 43.5 GHz	+75 dBm +70 dBm	IP ₃ • 100 kHz to 4 GHz • 4 GHz to 6 GHz • 6 GHz to 43.5 GHz +28 dBm +23 dBm +20 dBm
Amplitude Accuracy	100 kHz to 6 GHz • ± 2.0 dB	6 GHz to 20 GHz • ± 3.0 dB	RBW filter shape • Flat-Top windowing
Residual Responses REF LEVEL ≤ -20 dBm	• 100 kHz to 6 GHz • 6 GHz to 15 GHz • 15 GHz to 44 GHz	-110 dBm -100 dBm -90 dBm	
SSB Phase Noise at 1 GHz Center Frequency	Offset Frequency • 10 Hz • 100 Hz • 1 kHz • 10 kHz • 100 kHz • 1 MHz	dBc/Hz -76 -108 -125 -136 -138 -138	
Lo Leakage at RF Input	• 100 kHz to 6 GHz • 6 GHz to 24 GHz • 24 GHz to 43.5 GHz	-80 dBm -50 dBm -75 dBm	
Spurious Mixer Responses	• 100 kHz to 6 GHz • 6 GHz to 24 GHz • 24 GHz to 43.5 GHz	-55 dBc -45 dBc -45 dBc	
Sub-Octave Preselector Filters	20 MHz to 43.5 GHz		
Synchronization	External trigger, GPIO, Internal GPS (+/-40ns)		
Operating Temperature	Standard (passive cooling) 32°F to 122°F (0°C to +50°C)		
Size and Weight	• 10.45" x 7.2" x 2.15" (265mm x 183mm x 55mm) • 7.77 lbs. (3.52 kg)		
Power Consumption	• 9 to 16 VDC • 33 Watt Maximum		
Interface	10GbE SFP+ port		
System Requirements	Windows or Linux Operating System, x64_86 architecture		

Ordering Options

Standard, Temperature Range 32°F to 122°F (0°C to +50°C)

Option 1, Temperature Range -40°F to 149°F (-40°C to +65°C)

Option-80 – IF Output Option (800MHz BW of IF tunable between 24GHz – 43.5GHz)